




D1110 (鉚合無螺絲)



D112X (鉚合鎖螺絲)



D113X (鉚合附螺絲)



MATERIALS:

- Housing: Thermoplastic (UL 94V-0)
- Contacts: Brass, Gold Plated on Contact Area
Sn Plated on Solderails
Nickel Under Plated Over All
- Shell: SPCC, Nickel Plated
- Rivet: Copper Alloy, Nickel Plated
- Board Lock: SPCC, Sn Plated

SPECIFICATION:

- Contact Current Rating: 3A
- Dielectric Withstanding Voltage: AC 500V r.m.s.
- Insulation Resistance: 5000mΩ Min. at DC 500V
- Contact Resistance: 30mΩ Max.
- Operating Temperature: -55°C to 105°C

ORDER INFORMATION:

D 1 1 X X - 25 F - 1 X 0 R
① ② ③

- ① 1=W / O(Without Screw)
2=W / S(Lock Screw)
3= W / O(Annex Screw)

- ② 0=(Without Screw)
1=(4.8mm / 11.80mm) SPCC Screw
2=(5.8mm / 13.00mm) SPCC Screw
A=(4.8mm / 11.80mm) Copper Alloy Screw
B=(5.8mm / 13.00mm) Copper Alloy Screw

- ③ 1=Black / PBT
2=PC99 / PBT

XIAN YI PRECISION CO., LTD.
祥益精密股份有限公司

TITLE / 品名: D-Sub 25F(8.08mm) Right Angle(R/A) Dip Type Connector

PART NO / 料號: D11XX-25F-1X0R

APPROVE / 核準	CHECKED / 審查	DRAWING / 繪圖	DRAWING NO / 圖號	UNIT / 單位		GENERAL TOLERANCE X ±0.50 .X ±0.38 .XX ±0.20 .XXX ±0.10	A.0 圖面發行	2011/05/09
James	James	Chenrong	L-005	mm				

核準發行章
僅供參考