



D114X (叉鎖)

**MATERIALS:**

- Housing: Thermoplastic (UL 94V-0)
- Contacts: Brass, Gold Plated on Contact Area  
Sn Plated on Solderails  
Nickel Under Plated Over All
- Shell: SPCC, Nickel Plated
- Board Lock: SPCC, Sn Plated

**SPECIFICATION:**

- Contact Current Rating: 3A
- Dielectric Withstanding Voltage: AC 500V r.m.s.
- Insulation Resistance: 5000mΩ Min. at DC 500V
- Contact Resistance: 30mΩ Max.
- Operating Temperature: -55°C to 105°C

**ORDER INFORMATION:**

D 1 1 4 X - 25 F - 1 X 0 R

① ②

- ① 1=(4.8mm / 11.80mm) SPCC Screw  
2=(5.8mm / 13.00mm) SPCC Screw  
A=(4.8mm / 11.80mm) Copper Alloy Screw  
B=(5.8mm / 13.00mm) Copper Alloy Screw

- ② 1=Black / PBT  
2=PC99 / PBT

**XIAN YI PRECISION CO., LTD.**  
祥益精密股份有限公司

TITLE / 品名: D-Sub 25F(8.08mm) Right Angle(R/A) Dip Type Connector

PART NO / 料號: D114X-25F-1X0R

APPROVE / 核准	CHECKED / 審查	DRAWING / 繪圖	DRAWING NO / 圖號	UNIT / 單位	GENERAL TOLERANCE		NO. REV / 版本		修訂內容		日期	
James	James	Chenrong	L-006	mm	X ±0.50 .X ±0.38 .XX ±0.20 .XXX ±0.10	△		A.0	圖面發行	2011/05/09		
SHEET 1 OF 1												

僅供參考 核準發行章